

BETONAC®-AL

CONCRETE AND RUST REMOVER FOR TRUCKS, EQUIPMENT AND MOULDS WITH PROTECTION AGAINST ATTACK ON ALUMINIUM

Product Description

BETONAC®-AL is designed to clean machinery and in particular aluminium parts which cannot be cleaned with other caustic cleaners. BETONAC®-AL has special inhibitors that protect the aluminium parts during the prescribed application time.

Uses

BETONAC®-AL is designed to remove concrete, lime scale, boiler scale and rust from construction equipment, formwork parts, tools, vehicle panels and concrete moulds. It is designed to not effect aluminium and alloy parts on machinery.

- Special Inhibitors are used to protect aluminium, with no detriment to the cleaning capacity
- A variety of applications - construction equipment, formwork, tools, vehicles, pipes and stands
- Quickly and easily dissolves areas of concrete, rust, lime scale and calcium
- Highly active concentrate
- Cuts working time
- Economical - dilutes up to 7 times with water

Advantages

- Economical – comes in concentrated form
- Short impact time
- Highly active
- Easy to use

Technical Data

Appearance/Colour

Colourless

Density

1,52 g/ml

Dilution

1:5 – 1:10 with water

pH value

0,5

Storage/Shelf life

Store in a cool dry place, protect from frost. Minimum shelf life 30 months in original sealed container.

Application

General information

If a false floor is placed on the bottom of the dipping container, any washed contamination can easily be removed, so the BETONAC®-AL is not neutralized and can work more efficiently, and on numerous occasions.

Leycochem LEYDE-Iraq

Tel.: 0750-4344200, Tel.:0770-8748222, Tel.:0781-3802151

Email: sales.leycochem.iraq@leyde.com

www.leyde.com

LeycoChem LEYDE GmbH Germany

Industriestrasse 155

P.O. Box 501627

D-50999 Köln/Cologne

Tel.:+49(0)2236-96600-0

Fax:+49(0)2236-96600-10

Email: leycochem@leyde.com

Product Data Sheet

Product No: 02.060

Dosage

BETONAC®-AL should be mixed 1:5 to 1:10 with water. Parts should be dipped between 30 minutes and 4 hours, depending on the degree of contamination.

Important Note

Tin, Zinc, brass, nickel, galvanized parts and precision instruments as well as hydrocarbon hardened shovels should not be dipped.

Safety Instructions

Ecology

BETONAC®-AL will neutralize with use, though regard for local water authority regulations should be taken when disposing of the used product.

Safety precautions

Use BETONAC®-AL in a well-ventilated area, wear suitable PPE and refer to material safety data sheet.

Legal notes

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 01.09.2009